# 1N0GRGC

## GAS CHARGRILL



Grill range made of AISI 304 stainless steel, 20/10 mm thickness top. Cooking griddle made of enamelled cast iron with special nanotechnology surface treatment for a better fats sliding, delivered with stainless steel splash guards and cleaning brush. 2 independent burners with thermocouple pilot light and piezo-electric ignition. The cooking grill is heated by radiation from the metal profiles heated by the burner.

| | | | |
|---|---|---|---|
| *Gas power < 35 kw* | Yes | *Power supply* | Gas |
| *Worktop thickness* | 2 mm | | |

### Functional features

- Grill suitable for cooking meat, fish and vegetables for the most discerning palates thanks to the combination of radiating and contact cooking.
- n. 2 burners with adjustable power each from 6 to 12.5 kW.
- Specific output per useful surface dm² 549 W.
- Grill dimensions 67x70 cm.
- Cooking grills made in iron with a nanotechnology surface treatment which improves run-off of fats and grease by up to 8% compared to standard treatments.
- Cooking grids are made in cast iron with adjustable gradient on 2 levels, they are reversible with two different sections.
- The grill is heated by radiation from metal profiles heated by the burner.
- Cooking grid, burner, metal profiles and splash guard are all fully removable.
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Good thermal insulation on the front of the appliance for a greater comfort of the operator.
- Splash guard on three sides in AISI 304 stainless steel, with concave geometry to contain splashes and heat.
- Pull-out drawer, to the entire depth of the grid, made of stainless steel, for collecting cooking residues, positioned under each individual burner. Flame zone protected against falling cooking fats; easily removable without tools. Pull-out drawer capacity: 1.5 lt.
- Two double flame stainless steel burners.
- Piezoelectric ignition with button guard, frontal visibility of the flames, possibility of manual ignition of the pilot light from the front panel.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Access to all components through front compartment or control console.

### Safety equipment and approvals

- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- IPX5 protection rating.

### Standard equipment

- Brush for cleaning.

### Optionals and Accessories

- Serving shelf for condiments and raw or cooked foods; grill lift accessory for adjusting the inclination.

# 1N0GRGC

## Technical Data

| | | | |
|---|---|---|---|
| *Gas Power* | 25 kW | *Dimensions* | 80x92x25 cm |
| *Packing* | 86x102x68 cm | | |