

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 60 CM WITH WORKTOP

Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by air. Automatic condensation evaporation. Digital thermometer-thermostat. One-piece structure in AISI 304 stainless steel. 3 doors.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Depth with door open (cm)</i>	96
<i>Energy consumption, kWh/24h</i>	2,433	<i>Energy consumption/year, kWh/a</i>	888
<i>Energy Efficiency Class</i>	C	<i>Energy Efficiency Index</i>	38,21
<i>Heavy duty cabinets</i>	This appliance is intended for use in ambient temperatures up to 40 °C	<i>LWA dB(A)</i>	50
<i>Net usable volume, lt</i>	209	<i>N° doors</i>	3
<i>N° drawers</i>	0	<i>Refrigerant charge, kg</i>	0,07
<i>Refrigerant/GWP</i>	R290/3	<i>Refrigeration power at -10°C W</i>	465
<i>Temperature range</i>	0/+10°C	<i>Volume, gross, lt</i>	353

Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid cm 32.5x46.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	125 kg
<i>Gross Weight</i>	137 kg	<i>Electric Power</i>	0,28 kW

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 60 CM WITH WORKTOP

Refrigerated counters

5MJBM



Dimensions

185x60x90 cm

Packing

189x64,5x100,5 cm

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 60 CM WITH WORKTOP
Refrigerated counters



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

29/04/2022