

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP

One-piece structure made in special anti-fingerprint steel. CFC-free polyurethane insulation, 60 mm thick. Easy removable AISI 304 stainless steel rack bars. Automatic defrosting system by air. Automatic condensation evaporation. Supplied as standard each compartment: 2 AISI 304 stainless steel runners + 1 shelf. Digital thermometer-thermostat. Without top. 2 doors, 2 drawers.



| | | | |
|---------------------------------------|---------------------|------------------------------------|--|
| <i>Climate class</i> | 5 (+40°C, 40% R.H.) | <i>Energy consumption, kWh/24h</i> | 2,973 |
| <i>Energy consumption/year, kWh/a</i> | 1085 | <i>Energy Efficiency Class</i> | C |
| <i>Energy Efficiency Index</i> | 46,29 | <i>Heavy duty cabinets</i> | This appliance is intended for use in ambient temperatures up to 40 °C |
| <i>LWA dB(A)</i> | 46 | <i>Net usable volume, lt</i> | 217 |
| <i>N° doors</i> | 2 | <i>N° drawers</i> | 2 |
| <i>Refrigerant charge, kg</i> | 0,07 | <i>Refrigerant/GWP</i> | R290/3 |
| <i>Refrigeration power at -10°C W</i> | 465 | <i>Temperature range</i> | 0/+10°C |
| <i>Volume, gross, lt</i> | 434 | | |

Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance' s outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.
- Key-lock: optional

Technical Data

| | | | |
|------------------------|-----------------|-----------------------|---------|
| <i>Working voltage</i> | 230V 1N~ / 50Hz | <i>Net Weight</i> | 119 kg |
| <i>Gross Weight</i> | 131 kg | <i>Electric Power</i> | 0,28 kW |



5VB2



Dimensions

185x70x84 cm

Packing

192x76x92 cm

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP Refrigerated counters



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

29/04/2022