

## REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP

One-piece structure made in special anti-fingerprint steel. CFC-free polyurethane insulation, 60 mm thick. Easy removable AISI 304 stainless steel rack bars. Automatic defrosting system by air. Automatic condensation evaporation. Supplied as standard each compartment: 2 AISI 304 stainless steel runners + 1 shelf. Digital thermometer-thermostat. One-piece structure in AISI 304 stainless steel. 2 doors, 4 drawers.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy consumption, kWh/24h</i>	4,31
<i>Energy consumption/year, kWh/a</i>	1573	<i>Energy Efficiency Class</i>	D
<i>Energy Efficiency Index</i>	63,18	<i>Heavy duty cabinets</i>	This appliance is intended for use in ambient temperatures up to 40 °C
<i>LWA dB(A)</i>	50	<i>Net usable volume, lt</i>	274
<i>N° doors</i>	2	<i>N° drawers</i>	4
<i>Refrigerant charge, kg</i>	0,08	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power at -10°C W</i>	560	<i>Temperature range</i>	0/+10°C
<i>Volume, gross, lt</i>	578		

### Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance' s outstanding reliability is also assured by the IP24 protection of its functional elements.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.
- Key-lock: optional

### Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	181 kg
------------------------	-----------------	-------------------	--------

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP

Refrigerated counters

# 5VC4M



Gross Weight	196 kg	Electric Power	0,32 kW
Dimensions	230x70x90 cm	Packing	236x76x92 cm

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP

Refrigerated counters

