

CUPBOARD BOTH SIDE SLIDING DOORS. TWO SIDED WORKTOP

AISI 304 stainless steel top 54 mm h with satin finish 12/10 mm thickness. Sound deadening waterproof panel underneath. AISI 304 stainless steel free-standing structure with satin finish, with sliding doors with double walled sandwich panel structure, middle shelf reinforced by omega. Double side opening. Height-adjustable stainless steel feet.





Rear splashback Working side Two working sides nο

Functional features

- · Sturdiness of the worktop due to the particular construction and use of AISI 304 stainless steel sheet, thickness 12/10 mm.
- Hygiene ensured by the materials used and by the totally "closed" structure of the worktop.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Height-adjustable stainless steel feet for leveling on the floor, equipped with a thermosetting plastic sole.
- Capacity in Ø 23 cm plates on the intermediate shelf: 324.
- Maximum load per shelf with evenly distributed load: 110 kg.
- Doors opening on two sides.

Constructional features

- Worktop height 54 mm made of 1.2 mm thick AISI 304 stainless steel with soundeadening water-proof panel.
- Self-supporting cabinet made entirely on sides, back, bottom and door in satin-finished and cold-bent AISI 304 stainless steel.
- Sliding doors, sliding on upper guides, double-skinned. Handle obtained by folding in a single piece with the door.
- Middle shelf that can be positioned in different heights made of AISI 304 stainless steel, with omega reinforcement.
- · Hexagonal feet in stainless steel with plastic sole, adjustable for leveling on the floor h = 150 (max h = 180) mm.

Safety equipment and approvals

The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Optional

Swivelling wheels with brake.

Technical Data

Net Weight	73,5 kg	Gross Weight	83,5 kg
Dimensions	100x70x90 cm	Packing	105x102x95 cm