

# N10043PB



## COLD ROOM THICKNESS PANEL 10 CM, INTERNAL HEIGHT 243 CM, 10 CBM WITH FLOOR



Plastified panels; thickness 10 cm; insulation in expanded polyurethane without using CFC and HCFC, density 40Kg / m<sup>3</sup>. DOOR - Useful opening cm 70x190h, hinged to the right and positioned on the longer side of the cold room. Semi-recessed door, overhang 4 cm. Round corner elements, both internally and externally. External handle with key and internal security release. With pedestrian non-slip floor. HACCP certification.



COLD ROOM THICKNESS PANEL 10 CM, INTERNAL HEIGHT 243 CM, 10 CBM WITH FLOOR

Cold rooms

<i>Door opening</i>	70x190 cm	<i>Floor</i>	Yes
<i>Inside height cm</i>	243 cm	<i>Panel thickness</i>	10 cm
<i>Precise load - floor</i>	100 Kg	<i>Temperature range</i>	+5/-20°C

### Functional features

- Key-lock and internal security release.
- DOOR - Useful light cm 70x190h, opening from left to right, positioned on the longer side of the cold room.
- Semi-recessed door, overhang 4 cm; advantage of less space outside, less volume to cool at the same flow rate and better seal thanks to the more sealant joint and to the larger magnetic gasket..
- Anti-slipable pedestrian FLOOR, polyurethane insulation density 40 kg / m<sup>3</sup>. Plated galvanized sheet metal 7/10, static capacity load 1500 Kg / m<sup>2</sup>, punctual precise capacity load 100Kg.

### Constructional features

- Insulation in polyurethane without CFC and HCFC 100 mm thickness, polyurethane insulation density 38/40 kg / m<sup>3</sup>; K = 0.208 W / m<sup>2</sup>K.
- Modular prefabricated panels made from food-approved, non-toxic plastic-coated plate.
- Fixing: with two-point fasteners with alignment system.
- Corner units: non-toxic plastic-coated plate cladding, polyurethane insulation, rounded on inside and outside.
- Patented panel fastening system that assures assembly speed and tightness guarantee.
- HACCP certification: the chamber is compliant with the HACCP International standards.

### Technical Data

<i>Net Weight</i>	570 kg	<i>Gross Weight</i>	600 kg
<i>Dimensions</i>	223x223x263 cm	<i>Packing</i>	246x122x166 cm