

**COLD ROOM THICKNESS PANEL 6 CM,  
INTERNAL HEIGHT 203 CM, 11,7 CBM**

Plastified panels; thickness 6 cm; insulation in expanded polyurethane without using CFC and HCFC, density 40Kg / m<sup>3</sup>. DOOR - Useful opening cm 70x190h, hinged to the right and positioned on the longer side of the cold room. Semi-recessed door, overhang 4 cm. Round corner elements, both internally and externally. External handle with key and internal security release. Version without floor and equipped with profiles and accessories for grounding. HACCP certification.



<i>Door opening</i>	70x190 cm	<i>Floor</i>	No
<i>Inside height cm</i>	203 cm	<i>Panel thickness</i>	6 cm
<i>Temperature range</i>	0/+5°C		

**Functional features**

- Key-lock and internal security release.
- DOOR - Useful light cm 70x190h, opening from left to right, positioned on the longer side of the cold room.
- Semi-recessed door, overhang 4 cm; advantage of less space outside, less volume to cool at the same flow rate and better seal thanks to the more sealant joint and to the larger magnetic gasket..
- Model without floor.

**Constructional features**

- Polyurethane insulation without CFC and HCFC thickness 60 mm, density 38/40 kg/m<sup>3</sup>; K = 0,336 W/m<sup>2</sup>K.
- Modular prefabricated panels made from food-approved, non-toxic plastic-coated plate.
- Fixing: with two-point fasteners with alignment system.
- Corner units: non-toxic plastic-coated plate cladding, polyurethane insulation, rounded on inside and outside.
- Patented panel fastening system that assures assembly speed and tightness guarantee.
- HACCP certification: the chamber is compliant with the HACCP International standards.

**Technical Data**

<i>Net Weight</i>	265 kg	<i>Gross Weight</i>	300 kg
<i>Dimensions</i>	295x215x209 cm	<i>Packing</i>	286x122x107 cm

COLD ROOM THICKNESS PANEL 6 CM, INTERNAL HEIGHT 203 CM, 11,7 CBM

Cold rooms