# **ANGELO PO**

# COLD ROOM THICKNESS PANEL 10 CM, INTERNAL HEIGHT 203 CM, 11,7 CBM WITH FLOOR

Plastified panels; thickness 10 cm; insulation in expanded polyurethane without using CFC and HCFC, density 40Kg / m³. DOOR - Useful opening cm 70x190h, hinged to the right and positioned on the longer side of the cold room. Semi-recessed door, overhang 4 cm. Round corner elements, both internally and externally. External handle with key and internal security release. With pedestrian non-slip floor. HACCP certification.





Door opening	70x190 cm	Floor	Yes
Inside height cm	203 cm	Panel thickness	10 cm
Precise load - floor	100 Kg	Temperature range	+5/-20°C

### **Functional features**

- · Key-lock and internal security release.
- · DOOR Useful light cm 70x190h, opening from left to right, positioned on the longer side of the cold room.
- Semi-recessed door, overhang 4 cm; advantage of less space outside, less volume to cool at the same flow rate and better seal thanks to the more sealant joint and to the larger magnetic gasket..
- Anti-slippable pedestrian FLOOR, polyurethane insulation density 40 kg / m³. Plated galvanized sheet metal 7/10, static capacity load 1500 Kg / m², punctual precise capacity load 100Kg.

## Constructional features

- Insulation in polyurethane without CFC and HCFC 100 mm thickness, polyurethane insulation density 38/40 kg / m3; K = 0.208 W / m2K.
- · Modular prefabricated panels made from food-approved, non-toxic plastic-coated plate.
- · Fixing: with two-point fasteners with alignment system.
- · Corner units: non-toxic plastic-coated plate cladding, polyurethane insulation, rounded on inside and outside.
- · Patented panel fastening system that assures assembly speed and tightness guarantee.
- · HACCP certification: the chamber is compliant with the HACCP International standards.

# **Technical Data**

	Net Weight	300 kg	Gross Weight	332 kg
	Dimensions	303x223x223 cm	Packing	286x122x181 cm