

REFRIGERATED TOP ON REFRIGERATED CUPBOARD - 4 GN

Printed top 3 cm deep, with rounded corners, capacity n.4 GN 1/1. Temperature range 0/ +8°C, 50 mm insulated. Digital temperatures control. Top in AISI 304 stainless steel, 1,5 mm thick. Lower cupboard: refrigerated version +4 +8 °C, digital temperature control. The block must necessarily be completed with paneling, choosing the type of panel preferred.



| | | | |
|-------------------------------|-------|--------------------|------|
| <i>Capacity</i> | 4 GN | <i>Refrigerant</i> | R290 |
| <i>Refrigerant charge, kg</i> | 0,075 | | |

Constructional features

- Top in AISI 304 stainless steel, 1,5 mm thick with sides preset to mechanical bayonet-type fitting. Top height 40 mm, front part in sight 85 mm.
- AISI 304 stainless steel pressed well with rounded corners, 30 mm deep.
- Cold compartment dimension 800x535x325H mm - N. 2 compartments GN 1/1.
- Independent digital temperature controls.

Technical Data

| | | | |
|------------------------|----------------------|-----------------------|---------------|
| <i>Working voltage</i> | 230V 1N~ / 50 ÷ 60Hz | <i>Net Weight</i> | 121 kg |
| <i>Gross Weight</i> | 133 kg | <i>Electric Power</i> | 0,2 kW |
| <i>Dimensions</i> | 150x83x90 cm | <i>Packing</i> | 155x88x108 cm |

REFRIGERATED TOP ON REFRIGERATED CUPBOARD - 4 GN
Self-Service and Drop-in