










POS.	DESCRIPTION	N°	CODE
1	INOX FEET	4	3439700
2	LEFT BASE SUPPORT	1	3467600
3	GRAPHITE GASKET	2	3215080
4	FLUE GAS TUBE	1	3392200
5	FLUE GAS TUBE	1	3392200
6	FLANGED NUT INOX M5	8	3110280
7	RIGHT BASE SUPPORT	1	3467620
8	STEAM DIVERTER	1	3467610
9	AIR INLET TUBE	1	3392210
10	STEAM EXHAUST TUBE	1	3412710
11	ISOLANT PANEL	1	3412750
12a	FAN 230V	1	32V5790
12b	FAN 120V	1	3081671
13	FIXING BRACKET	1	3373370
14	CABLE PROTECTION	1	3467630
15	FILTER SUPPORT	1	3373360
16	CABLES (USA)	1	3469780
16	CABLES (CE)	1	3469790
17	LEFT SIDE COVER	1	3467680
18	FRONT COVER	1	3467660
19	RIGHT SIDE COVER	1	3467670
20	AIR INLET EXTENSION	2	3411180
21	TOP TUBES BRACKET	1	3467640
22	RUBBET EXTENSION TUBE	1	3126980
23	STEAM OUTLET	1	3238920
24	RUBBET EXTENSION TUBE	1	111AA08
25	STEAM OUTLET PIPE	1	3174360
26	TUBES EXTERNAL PROTECTION	1	3467650
27	SCREW M5x12	12	3170380
28	WASHER Ø5	12	3120070
29	SCREW M4x50	2	31A7270
30	METAL CLAMP Ø 50x70	2	3140160
31	METAL CLAMP Ø 60x80	2	3374250
32	WASHER Ø 4	2	3120090
33a	RUBBER CABLE GLAND Ø 25	1	32X0140
33b	RUBBER CABLE GLAND Ø 32	1	32X0130
34	SCREW TCB	10	31E0030




Bottom Oven




Upper Oven


ATTENTION: before starting, remove all the protective film from the kit components.




Prepare the bottom oven




Remove all the feet



Install the new feet provided with the kit




Set the foot height to 150 mm







Screw the new feet















Remove the evacuation tube protection, remove the rivet with a drill and detach the protection stick.




Remove all the screw from the top cover of the oven














Prepare the cooking chamber aspiration tube, use high temperature RTV silicone




Prepare the cooking chamber aspiration tube, use high temperature RTV silicone









If the upper oven is gas, fit the 120V fan. If the upper oven is electric, fit the 230V fan.




PREPARE THE TOP OVEN






Remove the left side panel unscrewing the two screw placed on the bottom side




Set the feet height to 123 mm







Remove the air filter (the entire plastic box) unscrewing the four screw











Place the top oven using the feet references on the base supports




















Place the air extension support






































Predispose the front cover for the LDRAT.











PROPERLY ASSEMBLED

FRONT



RIGHT



REAR



LEFT

