04WFR3ED



ELECTRIC FRYER 1 WELL 9 L DIGITAL CONTROLS

18-10 Stainless Steel structure,20/10 mm thickness top. Pressed well sealed into top, generously coved with drain zone. Under cabinet,side walls, bottom in a single radiused piece with insulated hinged doors and and heatresistant chromium-plated handles.Delivered with 1 basket/each well. Electronic circuit board for control and display temperature 0-190°C, melting and 100°C hold function programming, sound alarm.

Control paneldigitalEnergy ControlPre-Setting for remote control of power peaksLiter each well9Power supplyElectricityProduct fitting upwith integrated undercompartmentProductivity15 kg/h french friesWell quantity1Verlage400Y 3N~/ 230V 3~/ 50÷60 HzNet Weight65 kgForss Weight73 kgElectric Power7,3 kWDimensions40x110x72 cmPacking130x46x117 cm				
Product fitting upwith integrated undercompartmentProductivity15 kg/h french friesWell quantity1Technical DataWorking voltage400V 3N~ / 230V 3~ / 50÷60 HzNet Weight65 kgGross Weight73 kgElectric Power7,3 kW	Control panel	digital	Energy Control	-
Well quantity 1 Technical Data Working voltage 400V 3N~ / 230V 3~ / 50÷60 Hz Net Weight 65 kg Gross Weight 73 kg	Liter each well	9	Power supply	Electricity
Technical Data Working voltage 400V 3N~ / 230V 3~ / 50÷60 Hz Net Weight 65 kg Gross Weight 73 kg Electric Power 7,3 kW	Product fitting up	0	Productivity	15 kg/h french fries
Working voltage400V 3N~ / 230V 3~ / 50÷60 HzNet Weight65 kgGross Weight73 kgElectric Power7,3 kW	Well quantity	1		
Working voltage400V 3N~ / 230V 3~ / 50÷60 HzNet Weight65 kgGross Weight73 kgElectric Power7,3 kW				
Gross Weight 73 kg Electric Power 7,3 kW	Technical Data			
	Working voltage	400V 3N~ / 230V 3~ / 50÷60 Hz	Net Weight	65 kg
Dimensions 40x110x72 cm Packing 130x46x117 cm	Gross Weight	73 kg	Electric Power	7,3 kW
	Dimensions	40x110x72 cm	Packing	130x46x117 cm

