

ELECTRIC BAIN MARIE

Wett well bain marie with structure made of AISI 304 stainless steel, 20/10 mm thickness top. Pressed well integrated and sealed into top with satin polished finish. Useful to containers GN 1/1 + 1/3 or sub-multiples. Indirect heating controlled by operation thermostat 30-100°C and safety thermostat. Containers not supplied. Pre-setting for remote control of power peaks.



<i>Energy Control</i>	Pre-Setting for remote control of power peaks	<i>Power supply</i>	Electricity
<i>Well quantity</i>	1	<i>Worktop thickness</i>	2 mm

Functional features

- Internal well capacity 30.5x68.6x16 cm - 1/1GN + 1/3GN
- Water capacity indicated by operating level 5 litres
- Thermostatic temperature control from 30° to 100°C.
- Optimum insulation of the heating chamber underneath the well with a 20% increase in efficiency and energy savings up to 25%.
- Specific heating output 1000 watt/litre.
- Pre-setting for remote control of power peaks.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.
- Well in AISI 304 stainless steel thickness 12/10, pressed with rounded corners.
- Front-mounted drain cock with rotary control to prevent accidental opening.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.

Safety equipment and approvals

- Maximum temperature safety thermostat at minimum allowed water level (pressed on well).
- Appliance can not be used without water.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Optionals and Accessories

- False base.
- Gn containers (h= 20/40/65/100/150 mm) - 1/1, 1/3, 1/2, 2/3, 1/4, 1/6.
- Cross bars for containers.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50 ÷ 60Hz	<i>Net Weight</i>	29 kg
<i>Gross Weight</i>	34 kg	<i>Electric Power</i>	2,55 kW
<i>Dimensions</i>	40x92x25 cm	<i>Packing</i>	102x46x68 cm