

ELECTRIC GRIDDLE WITH SMOOTH MILD STEEL PLATE



Available only for countries outside the European Community. Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Satin finished Fe510D steel cooking plate. COOKING-PRO SYSTEM. Delivered with: plate plug. Heating by heating elements made in AISI 309 stainless steel, safety thermostat. Working temperature (min-max): 70-260°C. Pre-setting for remote control of power peaks.



Energy Control	Pre-Setting for remote control of power peaks	Plate	Fe510D - smooth
Power supply	Electricity	Worktop thickness	2 mm

Functional features

- Smooth cooking plate made in special Fe510D steel thickness 15 mm.
- Plate sealed and slightly recessed into the worktop, obtained by a special mould (Hygienic Design patented), satin-finished.
- Working temperature (min-max): 70-260°C.
- Cooking plate surface 315x635 mm.
- Specific output per useful surface dm² 255 W.
- n. 1 independent cooking area power rated at 5.1 kW
- COOKING PRO system ensures high performances, exceptional cooking uniformity, instant temperature recovery for continuous results and energy savings up to 20%. Electric elements are incorporated in an innovative multilayered material ensuring quick temperature rise, high efficiency in the heat transfer, temperature stability and energy efficiency.
- EASY-WASH: this is the program to clean the cooking plate bringing the surface temperature up to 75°C, in order to wash it reducing water and detergent.
- Commutable to 230V3 50/60 Hz
- Provision for remote peak power cut.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1 lt.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Available only for countries outside the European Community.
- Safety thermostat protecting the appliance and electric parts.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

Working voltage	400V 3N~ / 230V 3~ / 50÷60 Hz	Net Weight	60 kg
Gross Weight	65 kg	Electric Power	5,1 kW
Dimensions	40x92x25 cm	Packing	102x46x67 cm