

## GAS GRIDDLE WITH SMOOTH MILD STEEL PLATE



Available only for countries outside the European Community. Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Satin finished Fe510D steel cooking plate. Delivered with: plate plug. Heating by burner group controlled by modulating thermostat valve. Working temperature (min-max): 120-320°C.



Plate	Fe510D - smooth	Power supply	Gas
Worktop thickness	2 mm		

### Functional features

- Smooth cooking plate made in special Fe510D steel thickness 15 mm.
- Plate sealed and slightly recessed into the worktop, obtained by a special mould (Hygienic Design patented), satin-finished.
- Working temperature (min-max): 120-320°C.
- Cooking plate surface 315x635 mm.
- Specific output per useful surface dm<sup>2</sup> 500 W.
- n. 1 independent cooking area power rated at 10.5 kW
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Combustion chambers separated for each burner to optimize both the yield and the gas consumption.
- Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1 lt.
- Electronic spark ignition, manual ignition allowed.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Access to all components through front compartment and control console.

### Safety equipment and approvals

- Available only for countries outside the European Community.
- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

### Technical Data

Working voltage	230V 1N~ / 50 ÷ 60Hz	Net Weight	60 kg
Gross Weight	65 kg	Electric Power	0,001 kW
Gas Power	10,5 kW	Dimensions	40x92x25 cm
Packing	102x46x68 cm		

GAS GRIDDLE WITH SMOOTH MILD STEEL PLATE

Icon9000 prof.900 - 2 mm