# **ONOSPE**

TOP

F



## **ELECTRIC CHIP SCUTTLE**

Chip scuttle made of AISI 304 stainless steel, 20/10 mm thickness top. Pressed well sealed into top with satin polished finish, useful for GN 1/1 containers max high 160 mm. Loading capacity: max 4 kg (potato chips). Delivered with a false bottom for oil dripping. Heating by an infrared lamp.





	Power supply	Electricity	Worktop thickness	2 mm						
F	Functional features									
	Electric chip scuttle made of AISI 304 stainless steel.									
	Heating by infrared lamp, po	owered 1 kw. 750°C.								

- Well dimensions: 305 x 510 mm, useful to GN 1/1 containers max high 160 mm.
- · Loading capacity: max 4 kg (potato chips).
- Energy consumption optimized by a power regulator.
- · High performances and efficiency in relation to the working power.

### **Constructional features**

- · Work top made in AISI 304 stainless steel, 20/10 thickness, with Scotch Brite finish with condensation collection recess.
- · Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- · Pressed well integrated to the top, sealed, satin gloss finish and rounded connection edges.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- · Rubber protection under the knobs against water infiltration.
- · Access to all components through front compartment and control console.

#### Safety equipment and approvals

- · The appliance conforms to the Appliances Directive also in case of water lack.
- · CE approvals in respect of all directives and regulations.
- · Approval to European Standard EN 1672-2 Hygienic Design.
- · IPX5 protection rating.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

#### Standard equipment

· Delivered with a false bottom for oil dripping.

Technical Data					
Working voltage	230V 1N~ / 50 ÷ 60Hz	Net Weight	20 kg		
Gross Weight	25 kg	Electric Power	1 kW		
Dimensions	40x92x25 cm	Packing	47x102x68 cm		

