

SOLID TOP ELECTRIC BOILING TABLE

Solid boiling range made of AISI 304 stainless steel structure, 20/10 mm thickness top. Radiant plate made of 16 Mo5 steel. Heating by brazed-welded heating elements. Independent temperature control on different working area. Pre-setting for remote control of power peaks.



Energy Control	Pre-Setting for remote control of power peaks	Power supply	Electricity
Worktop thickness	2 mm		

Functional features

- Solid boiling table, cooking plate with 2 heating areas, independent temperature control on each area.
- Cooking plate made of alloyed steel (16 Mo5), thickness 15 mm that guarantees a high yield compared to the employed power.
- n. 2 independent cooking areas power rated at 3 kW each
- Cooking plate surface 325 x 650 mm, useful surface 19.3 dm².
- Specific output per useful surface dm² 310 W.
- Heating elements with brazewelded resistances that guarantee quick response times and high efficiency, temperature control from 30°C to 360°C.
- Insulating panel placed below the heating elements to minimize heat loss and maximize efficiency.
- Provision for remote peak power cut.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Solid boiling range made in AISI 304 stainless steel, 20/10 mm thickness top, Scotch brite finishing.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Access to all components through front compartment and control console.
- The steel plate, the heating elements and working thermostats and over heating thermostats, is removable from above without the need to remove the appliance from the structure.
- Air filter (dishwasher safe) placed on the appliance bottom with an easy access is equipped with a spring clip facilitating assembly and disassembly operations.

Safety equipment and approvals

- Safety thermostat protection against over heating in case of working thermostat failure.
- Fan for the cooling the compartment housing the components with removable and dishwasher safe suction filter.
- Indicator light for over heating components compartment.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

Working voltage	400V 3N ~ 50 ÷ 60 Hz	Net Weight	35 kg
Gross Weight	41 kg	Electric Power	6 kW
Dimensions	40x92x25 cm	Packing	45x102x68 cm