

COUNTER TOP SOLID GAS RANGE

Solid boiling range made of AISI 304 stainless steel structure, 20/10 mm thickness top. Radiant plate made in cast iron. Heating by central stainless steel burner controlled by safety valve, pilot light and thermocouple. Electronic spark ignition.



Power supply	Gas	Worktop thickness	2 mm
--------------	-----	-------------------	------

Functional features

- Solid gas boiling table equipped with radiant plate.
- Radiant plate constructed in G.26 cast iron thickness 40 mm.
- Cooking plate featuring differentiated constant heating zones radiating from centre at 400°C towards the edges; removable disc placed in the centre of the plate, 130 mm diameter.
- Cooking plate surface 388 x 774 mm, useful surface 25.7 dm².
- Specific output per useful surface dm² 252 W.
- Heating by central burner with stabilised flame cone.
- Plate combustion chamber made of AISI 430 stainless steel, insulated to guarantee not to heat transmission to the work top.
- n. 1 burner, under the plate, power output 6.5 kW, heating output at min position 2.6 kW, electronic continuous spark ignition and manual ignition of the pilot flame by removing the central disc.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Access to all components through front compartment and control console.
- Sealed flue on the top.
- The steel plate, the heating elements and working thermostats and over heating thermostats, is removable from above without the need to remove the appliance from the structure.

Safety equipment and approvals

- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

Working voltage	230V 1N~ / 50 ÷ 60Hz	Net Weight	35 kg
Gross Weight	41 kg	Electric Power	0,001 kW
Gas Power	6,5 kW	Dimensions	40x92x25 cm
Packing	45x102x68 cm		

COUNTER TOP SOLID GAS RANGE
Icon9000 prof.900 - 2 mm