

WOK INDUCTION PYROCERAM COOKING RANGE



Electric range with pyroceram surface with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking surface with wok Ø 300 mm in pyroceram. Induction heating. Kettle recognition sensor and automatic check devices. Forced cooling of electronic components. By the electromagnetic induction, pots of suitable material are required.



Power supply	Electricity	Worktop thickness	2 mm
--------------	-------------	-------------------	------

Functional features

- Induction wok diameter 30 cm rated at 5 kW.
- Potentiometer with continuous power regulation from 1 to 10 kW.
- Very low radiation of heat to the environment and greater comfort for the operator, as all the power and heat are supplied to the base of the pan.
- Electronic diagnostic system with signaling alarm code through light on the controle console.
- Indirect cooking (not with contact) in pans certified for use on induction appliances.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Cooking plate in pyroceram flush and sealed with worktop, 30 cm diameter.
- Fan for the cooling the compartment housing the components with removable and dishwasher safe suction filter.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Over temperature device on the glass for cutting power in case of abnormal operation.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Optional

- Wok pan for induction appliances.

Technical Data

Working voltage	400V 3~ / 50Hz ÷ 60Hz	Net Weight	40 kg
Gross Weight	45 kg	Electric Power	5 kW
Dimensions	40x92x25 cm	Packing	45x102x70 cm