

## INFRARED PYROCERAM COOKING RANGE 2 AREAS



Electric range with pyroceram surface with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking surface in pyroceram, flush with worktop and sealed. Heating by infrared electric elements. 2 cooking independent areas controlled by energy regulator.



<i>Power supply</i>	Electricity	<i>Product fitting up</i>	Counter Top
<i>Worktop thickness</i>	2 mm		

### Functional features

- Cooking surface in pyroceram, flush with worktop and sealed.
- n. 2 independent cooking areas power rated at 2.5 kW each
- Power regulator, 10 levels.
- Electronic diagnostic system with signaling alarm code through light on the controle console.
- Indirect cooking.
- Heating by incandescent heating elements.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Commutable to 230V 3F 50/60 Hz
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Pyroceram glass, thickness 6 mm, max load weight: 0.2 kg/cm<sup>2</sup>.
- Glass surface dimension: 32 x 56 cm.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

### Safety equipment and approvals

- Thermal protection for over temperature.
- Residual heat indicator light under glass.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

### Technical Data

<i>Working voltage</i>	400V 3N~ / 230V 3~ / 50+60 Hz	<i>Net Weight</i>	30 kg
<i>Gross Weight</i>	37 kg	<i>Electric Power</i>	5 kW
<i>Dimensions</i>	40x72x25 cm	<i>Packing</i>	46x82x65 cm