

## GAS WET WELL BAIN-MARIE

Wett well bain marie with structure made of AISI 304 stainless steel, 30/10 mm thickness top. Pressed well integrated and sealed into top with satin polished finish. Useful to containers GN 1/1 + 1/3 or sub-multiples. Indirect heating controlled by operation thermostat 30-100°C and safety thermostat. Containers not supplied.



|                   |      |               |   |
|-------------------|------|---------------|---|
| Power supply      | Gas  | Well quantity | 1 |
| Worktop thickness | 3 mm |               |   |

### Functional features

- Internal well capacity 30.5x68.6x16 cm - 1/1GN + 1/3GN
- Water capacity indicated by operating level 5 litres
- Thermostatic temperature control from 30° to 100°C.
- Electronic spark ignition, manual ignition allowed.
- Specific heating output 1000 watt/litre.

### Constructional features

- Work top made in AISI 304 stainless steel, 30/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.
- Well in AISI 304 stainless steel thickness 12/10, pressed with rounded corners.
- Front-mounted drain cock with rotary control to prevent accidental opening.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.

### Safety equipment and approvals

- Maximum temperature safety thermostat at minimum allowed water level (pressed on well).
- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- Appliance can not be used without water.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

### Optional

- False base.
- Gn containers (h= 20/40/65/100/150 mm) - 1/1, 1/3, 1/2, 2/3, 1/4, 1/6.
- Cross bars for containers.

### Technical Data

|                 |                      |                |             |
|-----------------|----------------------|----------------|-------------|
| Working voltage | 230V 1N~ / 50 ÷ 60Hz | Net Weight     | 18 kg       |
| Gross Weight    | 21 kg                | Electric Power | 0,001 kW    |
| Gas Power       | 5 kW                 | Dimensions     | 40x92x25 cm |
| Packing         | 102x46x68 cm         |                |             |

GAS WET WELL BAIN-MARIE  
Icon9000 prof.900 - 3 mm