

INFRARED PYROCERAM COOKING RANGE 2 AREAS

Electric range with pyroceram surface with AISI 304 stainless steel structure, 30/10 mm thickness top. Cooking surface in pyroceram, flush with worktop and sealed. Heating by infrared electric elements. 2 cooking independent areas controlled by energy regulator. Pre-setting for remote control of power peaks.



Energy Control	Pre-Setting for remote control of power peaks	Power supply	Electricity
Worktop thickness	3 mm		

Functional features

- n. 2 independent cooking areas power rated at 3.4 kW each
- Incandescent electric elements with double circuit: internal diam. 19 cm, external diam. 27 cm.
- Double functionality: it is possible to use different types of pot on the same plate.
- Pre-setting for remote control of power peaks.
- Commutable to 230V 3F 50/60 Hz
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 30/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Cooking surface in pyroceram, thickness 6 mm, flush with worktop and sealed, max load weight: 0.2 kg/cm².
- Hob dimensions: 32 x 67 cm.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Thermal protection for over temperature intergated on the plate.
- Fan for the cooling the compartment housing the components with removable and dishwasher safe suction filter.
- Residual heat indicator light under glass.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

Working voltage	400V 3N ~ 50 ÷ 60 Hz	Net Weight	40 kg
Gross Weight	45 kg	Electric Power	6,8 kW
Dimensions	40x92x25 cm	Packing	102x46x68 cm

INFRARED PYROCERAM COOKING RANGE 2 AREAS

Icon9000 prof.900 - 3 mm