

OPEN SINK 1 BOWL CM 40X50X25H LEFT DRAINER

AISI304 stainless steel radiused, pressed top with satin finish and rear splashback. Pressed bowl with a continuous weld bead to form a waterlight seal. Open cupboard with front cover panel and AISI304 stainless steel tubular legs, 50 mm Ø.



| | | | |
|----------------------|------|------------------------|-------------|
| <i>Drainer</i> | left | <i>Well dimensions</i> | 40x50x25 cm |
| <i>Well quantity</i> | 1 | | |

Constructional features

- Sink worktop: in pressed AISI 304 stainless steel, with rear splash back in a single piece with the worktop, which is 54 mm thick.
- Side drainer: with press-formed ridges, it slopes to drain water towards the sink and has omega-shaped stainless steel stiffeners.
- Sink: in AISI 304 stainless steel, it is inserted in the worktop by means of a robotic welding and cleaning process.
- A special sound-absorbent material is attached to the underside of each sink.
- Legs: in satin-finish tubular AISI 304 stainless steel, they are 50 mm in diameter. The feet offer height adjustment of +/- 3 cm and shall be fitted with a sole made of thermosetting plastic material.
- The special support-leg fitting system allows placement flush against the wall, even when it is not at a right angle to flooring (distance between leg and wall 27 mm).
- ACCESSORIES: Hot/cold water mixer tap unit or foot control-lever tap, fixed wall shower and trap, drain and overflow assembly. Lower shelves and side panels.

Technical Data

| | | | |
|-------------------|--------------|---------------------|--------------|
| <i>Net Weight</i> | 28 kg | <i>Gross Weight</i> | 30 kg |
| <i>Dimensions</i> | 120x70x90 cm | <i>Packing</i> | 140x75x45 cm |