

TABLE WITH DOUBLE-SIDED SURFACE 140 CM

AISI 304 stainless steel top 54 mm h with satin finish 12/10 mm thickness. Sound deadening waterproof panel underneath. The exceptionally sturdy structure of the work table guarantees suitability for loads up to 150 kg/mq max (uniformly distributed).



Working side

Two working sides

Functional features

- The exceptionally sturdy structure of the work table guarantees suitability for loads not exceeding 150 kg/mq (uniformly distributed).
- The special support-leg fitting system allows placement flush against the wall, even when it is not at a right angle to flooring (distance between leg and wall 43 mm).
- Adjustable feet in AISI 304 stainless steel for levelling by means of the thermosetting plastic sole.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Hygiene ensured by the materials used and by the totally "closed" structure of the worktop. Ease in cleaning thanks to features like the designed tubing legs.

Constructional features

- AISI 304 stainless steel top 54 mm h with satin finish 12/10 mm thickness. Sound deadening waterproof panel underneath.
- .
- Nr. 4 legs, built in satin-finish AISI 304 stainless steel tubing with a 50 mm circular section.

Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Optional

- The work-table may be completed with the following accessories: general drawer, a drawer capacity GN 1/1, drawer unit composed by 4 drawers GN 1/1, lower shelf and swivelling wheels.

Technical Data

<i>Net Weight</i>	28 kg	<i>Gross Weight</i>	30 kg
<i>Dimensions</i>	140x70x90 cm	<i>Packing</i>	144x72x23 cm

TABLE WITH DOUBLE-SIDED SURFACE 140 CM

700 line