

## ELECTRIC BAIN MARIE

Wett well bain marie with structure made of AISI 304 stainless steel, 20/10 mm thickness top. Pressed well integrated and sealed into top with satin polished finish. Useful to containers GN 1/1 + 1/3 or sub-multiples. Indirect heating controlled by operation thermostat 30-100°C and safety thermostat. Containers not supplied. Pre-setting for remote control of power peaks.



Energy Control	Pre-Setting for remote control of power peaks	Power supply	Electricity
Worktop thickness	2 mm		

### Functional features

- Internal well capacity 63x68.6x16 cm - 2 x 1/1 GN + 2 x 1/3GN
- Water capacity indicated by operating level 11 litres
- Thermostatic temperature control from 30° to 100°C.
- Optimum insulation of the heating chamber underneath the well with a 20% increase in efficiency and energy savings up to 25%.
- Specific heating output 725 watt/litre.
- Pre-setting for remote control of power peaks.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.
- Well in AISI 304 stainless steel thickness 12/10, pressed with rounded corners.
- Front-mounted drain cock with rotary control to prevent accidental opening.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Equipped with: longitudinal cross bar.

### Safety equipment and approvals

- Maximum temperature safety thermostat at minimum allowed water level (pressed on well).
- Appliance can not be used without water.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

### Optional

- False base.
- Gn containers (h= 20/40/65/100/150 mm) - 1/1, 1/3, 1/2, 2/3, 1/4, 1/6.
- Cross bars for containers.

### Technical Data

Working voltage	400V 3N~ / 230V 3~ / 50÷60 Hz	Net Weight	35 kg
Gross Weight	40 kg	Electric Power	5,1 kW
Dimensions	80x92x25 cm	Packing	102x86x68 cm

Icon9000 prof.900 - 2 mm  
ELECTRIC BAIN MARIE