1N0GRE



ELECTRIC GRILL

Electric grill with structure made of AISI 304 stainless steel, 20/10 mm thickness top. Cooking griddle made of enamelled cast iron with special nanotechnology surface treatment, equipped with stainless steel splash guards and cleaning brush. Heating by two independent tilting electric heating groups. Lower well, water filling through tap with adjustment knob, capacity 14 lt (overflow). Presetting for remote control of power peaks.







Energy Control	Pre-Setting for remote control of power peaks	Power supply	Electricity
Worktop thickness	2 mm		

Functional features

- Grill suitable for cooking meat, fish and vegetables for the most discerning palates thanks to the combination of radiating and contact cooking.
- Appliance functioning with water under the cooking surface for reducing fumes and fats collecting, thus to guarantee a correct
 product humidification, without the excessive weight loss of the food.
- · n. 2 cooking areas powered at 5.25 kW each.
- · Specific output per useful surface dm² 275 W.
- Grill dimensions 62x60 cm.
- Cooking grills made in iron with a nanotechnology surface treatment which improves run-off of fats and grease by up to 8% compared to standard treatments.
- · Well with water filling through tap with adjustment knob and direct drain controlled by closing with overflow.
- · Commutable to 230V3 50/60 Hz
- · Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- · Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- · Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- · Good thermal insulation on the front of the appliance for a greater comfort of the operator.
- · Well capacity up to overflow It 14.
- · Cooking grill, splash guards fully removable, tilting electric elements group.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- · Rubber protection under the knobs against water infiltration.
- · Access to all components through front compartment and control console.

Safety equipment and approvals

- · Security thermostat with automatic reset in case of drying functioning.
- · Safety thermostat protecting the appliance and electric parts.
- · CE approvals in respect of all directives and regulations.
- · Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- · IPX5 protection rating.

Standard equipment

· Brush for cleaning.

Technical Data

Working voltage 400V 3N~ / 230V 3~ / 50÷60 Hz Net Weight 105 kg



Icon9000 prof.900 - 2 mm

1N0GRE



Gross Weight	115 kg	Electric Power	10,5 kW
Dimensions	80x92x25 cm	Packing	102x87x68 cm