

4 PLATE ELECTRIC RANGE, ELECTRIC STATIC OVEN - 230V

Electric boiling range with AISI 304 stainless steel structure, 20/10 mm thickness top. Watertight fully sealed cast iron plates, fitted with thermal protection devices. Each plate is controlled by a 5-position switch. Electric static oven in AISI 430 stainless steel with thermostat, removable stainless steel guides useful for GN 2/1 containers.



Oven Type	Electric static oven 2/1GN	Power supply	Electricity
Worktop thickness	2 mm		

Functional features

- Nr. 4 cast iron square electric cooking plates, dimensions 29.5x29.5 cm.
- Each plate power rated at 4 kW; adjustable heating on 4 working-positions.
- Electric static oven rated at 5.4 kW
- Oven capacity: 1 container GN 2/1 on removable stainless steel container, adjustable at three height levels.
- Cooking oven temperature control from 80°C to 260°C with 3 working modes.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam, on multi-elements support.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- External panels in stainless steel, dashboard with side panels in AISI 304 stainless steel, Scotch Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Worktop with pressed recess for collection of juices and for cooking plate housing.
- Insulation beneath the cooking surface to reduce surface temperatures on the front and to improve user comfort.
- Oven cooking chamber made in AISI 430 stainless steel, thickness 10/10; dimensions 53.5x69x31 cm (GN 2/1).
- Oven double-walled door insulated with Heavy Duty hinges.
- Rubber gasket on the oven front to ensure a perfect closing.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).
- Sealed flue on the top.
- Access to all components through front compartment and control console.
- Maintenance of inner components does not require appliance displacement.

Safety equipment and approvals

- Safety thermostat, integrated to the plates, against overheating due to idling.
- Safety thermostat against oven overheating.
- Approval to European Standard EN 1672-2 Hygienic Design.
- CE approvals in respect of all directives and regulations.
- IPX5 protection rating.

Standard equipment

- Delivered with 1 chromium plated grid 2/1GN.

Technical Data

Working voltage	230V 3 ~ 50 ÷ 60 Hz	Net Weight	120 kg
Gross Weight	135 kg	Electric Power	21,4 kW
Dimensions	80x92x90 cm	Packing	86x102x131 cm