

ALL AREA INDUCTION PYROCERAM COOKING RANGE ON CABINET

Electric range with pyroceram surface with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking surface in pyroceram, flush with worktop and sealed. Induction heating. All area with 4 cooking independent areas. Kettle recognition sensors and automatic check devices. Forced cooling of electronic components. By the electromagnetic induction, pots (minimum Ø 120 mm) of suitable material are required. Lower compartment with one door on each side.



Power supply	Electricity	Worktop thickness	2 mm
--------------	-------------	-------------------	------

Functional features

- 4 cooking independent all area hobs, power rated 7 kW each.
- Potentiometer with continuous power regulation from 1 to 10 kW.
- Very low radiation of heat to the environment and greater comfort for the operator, as all the power and heat are supplied to the base of the pan.
- Electronic diagnostic system with signaling alarm code through light on the controle console.
- Indirect cooking (not with contact) in pans with minimum diameter 120 mm, with 4 pans side by side at the same time of the same maximum diameter of 300 mm, certified for use on induction appliances.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Rubber protection under the knobs against water infiltration.
- Lower compartment with one door on each side.
- Installations through suitable accessories: freestanding on feet, on multi-elements support, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- External panels in stainless steel, dashboard with side panels in AISI 304 stainless steel, Scotch Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- 2 cooking hobs with dimensions: 32 x 67 cm.
- Fan for the cooling the compartment housing the components with removable and dishwasher safe suction filter.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Greater safety in the working area ensured by three sensors positioned underneath the glass ceramic surface to prevent improper operation.
- CE approvals in respect of all current directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- Degree of protection IP24.

Technical Data

Working voltage	400V 3~ / 50Hz ÷ 60Hz	Electric Power	28 kW
Dimensions	80x92x75 cm	Packing	86x102x116 cm

ALL AREA INDUCTION PYROCERAM COOKING RANGE ON CABINET

Icon9000 prof.900 - 2 mm