

1S1FT5G



GAS GRIDDLE RIBBED CHROMIUM PLATE ON CABINET

Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Cooking plate made in Fe510D steel with hard chromium surface treatment. Delivered with: plate plug. Heating by two independent burner groups controlled by modulating thermostat valve, safety thermostat. Working temperature (min-max): 100-280°C. Integrated lower open compartment.



Plate	Cr - ribbed	Power supply	Gas
Product fitting up	with integrated undercompartment	Worktop thickness	2 mm

Functional features

- Ribbed cooking plate made in special Fe510D steel thickness 12 mm.
- Plate with mirror finish, recessed into the worktop; welded around the perimeter and sealed.
- Working temperature: 100 - 280°C.
- Dimensions of the cooking plate (W x D): 730 x 530 mm. Frontal simmering zone 50 mm.
- n. 2 independent cooking areas power rated at 7 kW each.
- Two burners with MCE multi-element combustion systems (three-flame burners), entirely designed in the factory, guarantees improved heat distribution over the cooking surface.
- Integrated lower open compartment.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Combustion chambers separated for each burner to optimize both the yield and the gas consumption.
- Fett drain outlet diameter 32 mm with removable heat-resistant food-grade plastic plug.
- Removable tray in the lower compartment, capacity 6 lt for cooking and washing liquids collection.
- Piezoelectric ignition and frontal visibility of the flame.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radius rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).
- Access to all components through front compartment or control console.

Safety equipment and approvals

- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- Max temperature safety thermostat.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Optionals and Accessories

- Splash guards, cleaning plate scraper and blades; pipe for the water discharge during the cleaning of the plate.
- The lower compartment can be fitted with doors, wheels.

Technical Data

Net Weight	85 kg	Gross Weight	100 kg
Gas Power	14 kW	Dimensions	80x72x90 cm



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

05/07/2023

GAS GRIDDLE RIBBED CHROMIUM PLATE ON CABINET

Icon 7000 prof. 700

1S1FT5G

Packing

86x82x130 cm



Icon 7000 prof. 700
GAS GRIDDLE RIBBED CHROMIUM PLATE ON CABINET



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

05/07/2023