

4 ELECTRIC PLATES RANGE ON CABINET

Electric boiling range with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking square plates made of cast iron, watertight, fitted with thermal protection devices, 7-position switch for each plate. Integrated lower open compartment.



Power supply	Electricity	Product fitting up	with integrated undercompartment
--------------	-------------	--------------------	----------------------------------

Worktop thickness	2 mm
-------------------	------

Functional features

- Nr. 4 cast iron square electric cooking plates, dimensions each plate 22.7 x 22.7 cm.
- Heating power of each plate: 2.6 kW, controlled by 7-position switch.
- Integrated lower open compartment.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Worktop with pressed recess for collection of juices and for cooking plate housing.
- Insulation to reduce surface temperatures on the front of the cooking top and to improve user comfort.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Safety thermostat, integrated to the plates, against overheating due to idling.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

Optional

- Water filling tap.
- The lower compartment can be fitted with doors, container rack, wheels.

Technical Data

Working voltage	400V 3N ~ 50 ÷ 60 Hz	Electric Power	10,4 kW
Dimensions	80x72x90 cm	Packing	86x82x130 cm