

4 ELECTRIC PLATES RANGE ON CABINET

Electric boiling range with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking square plates made of cast iron, watertight, fitted with thermal protection devices, 7-position switch for each plate. Integrated lower open compartment. Provision for remote peak power cut.



<i>Energy Control</i>	Pre-Setting for remote control of power peaks	<i>Power supply</i>	Electricity
<i>Product fitting up</i>	with integrated undercompartment	<i>Worktop thickness</i>	2 mm

Functional features

- Nr. 4 cast iron square electric cooking plates, dimensions each plate 22.7 x 22.7 cm.
- Heating power of each plate: 2.6 kW, controlled by 7-position switch.
- Integrated lower open compartment.
- Provision for remote peak power cut.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Worktop with pressed recess for collection of juices and for cooking plate housing.
- Insulation to reduce surface temperatures on the front of the cooking top and to improve user comfort.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).
- Access to all components through front compartment or control console.

Safety equipment and approvals

- Safety thermostat, integrated to the plates, against overheating due to idling.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

Optional

- Water filling tap.
- The lower compartment can be fitted with doors, container rack, wheels.

Technical Data

<i>Working voltage</i>	400V 3N ~ 50 ÷ 60 Hz	<i>Electric Power</i>	10,4 kW
<i>Dimensions</i>	80x72x90 cm	<i>Packing</i>	86x82x130 cm