1T0FT6E



-(1)

3 mm

D

ELECTRIC GRIDDLE SMOOTH/RIBBED CHROMIUM PLATE

Griddle made of AISI 304 stainless steel, 30/10 mm thickness top. Cooking plate made in Fe510D steel with hard chromium surface treatment. COOKING-PRO SYSTEM. Delivered with: plate plug. Heating by two independent heating elements made in AISI 309 stainless steel placed under the plate, safety thermostat. Working temperature (min-max): 70-260°C. Pre-setting for remote control of power peaks.

503		
Energy Control	Pre-Setting for remote control of power peaks	Plate Cr - smooth/ribbed

Worktop thickness

Functional features

Power supply

- · Cooking plate (2/3 smooth 1/3 ribbed) made in special Fe510D steel with hard chromium surface treatment, thickness 15 mm.
- Plate sealed and slightly recessed into the worktop, obtained by a special mould hygienic design patented, with hard-chromium treatment, satin-finished
- · Working temperature (min-max): 70-260°C.
- · Cooking plate surface 715x635 mm.
- Specific output per useful surface dm² 226 W.
- n. 2 independent cooking areas power rated at 5.1 kW each

Electricity

- COOKING PRO system ensures high performances, exceptional cooking uniformity, instant temperature recovery for continuous results and energy savings up to 20%. Electric elements are incorporated in an innovative multilayered material ensuring quick temperature rise, high efficiency in the heat transfer, temperature stability and energy efficiency.
- EASY-WASH: this is the program to clean the cooking plate bringing the surface temperature up to 75°C, in order to wash it
 reducing water and detergent.
- Commutable to 230V3 50/60 Hz
- · Provision for remote peak power cut.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- · Work top made in AISI 304 stainless steel, 30/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- · Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1.75 lt.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- · Rubber protection under the knobs against water infiltration.
- · Sealed flue on the top.
- · Access to all components through front compartment and control console.

Safety equipment and approvals

- · Safety thermostat protecting the appliance and electric parts.
- · CE approvals in respect of all directives and regulations.
- · Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- IPX5 protection rating.

Technical Data					
	Working voltage	400V 3N~ / 230V 3~ / 50÷60 Hz	Net Weight	80 kg	
	Gross Weight	85 kg	Electric Power	10,2 kW	



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90 web: www.angelopo.com - email: angelopo@angelopo.it 09/02/2021



Dimensions

80x92x25 cm

Packing

86x102x68 cm

🛆 ANGELO PO

Icon9000 prof.900 - 3 mm ELECTRIC GRIDDLE SMOOTH/RIBBED CHROMIUM PLATE

