

1T1FR2ED



ELECTRIC FRYER 2 WELLS 21+21 L DIGITAL CONTROLS

Fryer made of AISI 304 stainless steel, 30/10 mm thickness top. Pressed wells, sealed into top, generously covered with large drain zone; each well delivered with 2 baskets and 1 lid. Digital controls. Electronic circuit board for control and display temperature 0-190°C, melting and 100°C hold function programming, sound alarm. Tilting heating elements in the well. Pre-setting for remote control of power peaks.



Control panel	digital	Energy Control	Pre-Setting for remote control of power peaks
Liter each well	21	Power supply	Electricity
Productivity	72 kg/h french fries (AGA)	Well quantity	2
Worktop thickness	3 mm		

Functional features

- Electric fryer 2 wells made in AISI 304 stainless steel - capacity 21 + 21 lt
- Large recess in the upper section for oil expansion with the same capacity of the well.
- Heating by electrical heating elements fitted inside the well, which can be tipped vertically for easy cleaning.
- Fried potatoes productivity (base on AGA standards): 36 kg/h per well.
- Heat exchange surface area calculated for specific output of no more than 5 watt/cm² for a longer oil life.
- Electronic control of operating temperature from 0°C to 190°C with precision $\pm 1^\circ\text{C}$, display of set and operating temperatures.
- Electronic circuit control board with following functions: frying programs, "melting" program, hold program at 100°C and self-diagnostics for faults, sound alarm.
- Optimal functionality and easy cleaning due to absence of fixed back basket hanger.
- Installations through suitable accessories: freestanding on feet, on multi-elements support, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 30/10 thickness with Scotch Brite finish.
- External panels in stainless steel, dashboard with side panels in AISI 304 stainless steel, Scotch Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Oil drain pipe fixed to well, with ball-valve tap fitted with heat-resistant handle.
- Sealed flue on the top.
- Hinged doors, with sandwich panel, made in AISI 304 stainless steel, grip directly pressed on the door plate, easy to clean.

Safety equipment and approvals

- Safety thermostat
- Safety cut off when the electric elements are in the vertical position.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- IPX5 protection rating.

Standard equipment

- n.2 baskets each well, made in chromium-plated steel, dimensions 15x36.8x12 cm
- Well lid in AISI 304 stainless steel full covering of the well, it can be fitted under the fryer.
- Chromium-plated steel bottom mesh with basket support outside the well.
- Oil drainage line extension located inside the door, for safe and easy oil drainage of oil, even when hot, away from the fryer itself.

Optional

- Single basket in chromed steel.



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

07/05/2021

ELECTRIC FRYER 2 WELLS 21+21 L DIGITAL CONTROLS
Icon9000 prof.900 - 3 mm

1T1FR2ED



Technical Data

<i>Working voltage</i>	400V 3N~ / 50Hz	<i>Net Weight</i>	110 kg
<i>Gross Weight</i>	120 kg	<i>Electric Power</i>	36 kW
<i>Dimensions</i>	80x92x75 cm	<i>Packing</i>	92x101x116 cm

ELECTRIC FRYER 2 WELLS 21+21 L DIGITAL CONTROLS
Icon9000 prof.900 - 3 mm