20T1SCP



BASKET LIFT FOR 40 L PASTA COOKER WELL

Automatic basket lifter made of AISI 304 stainless steel, 30/10 mm thickness top. Three digital displays, each dedicated to a single basket, with relative selection and control keys for setting 3 cooking times each, automatic lowering of the basket at the start of cooking. It can be positioned on the right or on the left of a pasta cooker 40 liter well. To be equipped with the special lifting baskets.



Worktop thickness

3 mm

Functional features

- Three digital displays, each dedicated to a single basket, with relative selection and control keys for setting 3 cooking times each, automatic lowering of the basket at the start of cooking.
- Five seconds before the end of the set cooking time, an acoustic signal is activated and at the end of the set time the basket automatically rises to the dripping position; automatic lifting of the basket before the cooking time ends.
- · Stop button for immediate block of operation.
- · Power supply on and off button.
- · Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam, on multi-elements support.

Constructional features

- · Work top made in AISI 304 stainless steel, 30/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).
- The feet are supplied unassembled.

Safety equipment and approvals

- · Emergency stop button.
- · CE approvals in respect of all directives and regulations.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- Approval to European Standard EN 1672-2 Hygienic Design.
- · IPX5 protection rating.

Optionals and Accessories

· Cestelli per sollevatore automatico, kit da 3 o 6 cestelli.

Technical Data			
Working voltage	230V 1N~ / 50Hz	Electric Power	0,2 kW
Dimensions	20x92x90 cm	Packing	28x102x116 cm

