

REFRIGERATED COUNTER -2°C ÷ +10°C DEPTH 70 CM WITH WORKTOP

Refrigerated counter with internal and external one-piece structure made of AISI 304 stainless steel. Outside finned evaporator and motor fan. Automatic electric defrosting, automatic condensation evaporation. Termometro-termostato digitale con porta di comunicazione, segnalazione allarmi HACCP. Worktop made in AISI 304 stainless steel. 1 door, 2 drawers.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption E24, kW/h	1,63
Energy consumption/year, kW/h	629	Energy Efficiency Class	B
Energy Efficiency Index	27,8	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	46	Net usable volume, lt	137
N° doors	1	N° drawers	2
Refrigerant charge, kg	0,065	Refrigerant/GWP	R290/3
Refrigeration power at -10°C W	345	Temperature range	-2/+10°C
Volume, gross, lt	290		

Functional features

- With digital thermometer-thermostat with communication port, HACCP alarm signalling: high and low temperature, black-out, probe failure. These alerts are provided via visual and acoustic alarms; if the probe inside the chamber fails, the appliance continues operating on the basis of the mean compressor operating times prior to the malfunction.
- Automatic defrosting system by heating elements.
- Highly energy-efficient power unit, refrigerant fluid R134a.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire-proof assuring high shock resistance level.
- One-piece structure made of AISI 304 stainless steel, inner rounded corners, CFC-free expanded polyurethane insulation. Door, side panels and control panel with scotchbrite finishing. Polished interior finishing.
- Insulation thickness: 60 mm.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Doors equipped with a self-closing device for openings inferior to 90°, integrated AISI 304 stainless steel handle with easy grip; Easy Clean magnetic gasket, easily removable.
- Refrigerated compartment with 1 door and 2 drawers.
- Enclosed drawers with three-stage telescopic runners allowing containers to be lifted out vertically.
- Upper drawer dimensions cm 30.5 x 54.8 x 14.7 h; lower drawer dimensions cm 30.5 x 54.8 x 19.5 h.
- Refrigerated compartment with AISI 304 stainless steel easy removable racks to support grids/containers.
- Drain outlet for easy cleaning.
- Evaporator with an anti-corrosion treatment.
- Stainless steel height-adjustable feet (140 mm - 200 mm).

REFRIGERATED COUNTER -2°C ÷ +10°C DEPTH 70 CM WITH WORKTOP

Refrigerated counters

5DA2M



Standard equipment

- Each compartment with door is delivered as standard with n. 1 GN 1/1 plastified grid and a pair of AISI 304 stainless steel guides.

Optional

- Temperature recorder, print terminal, pedal opening, various containers and / or grids.
- Drawer accessories for the transformation of the door compartment into a drawer (in this case the conveyor panel on the inner ceiling of the appliance must be removed).

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	119 kg
<i>Gross Weight</i>	129 kg	<i>Electric Power</i>	0,19 kW
<i>Dimensions</i>	140x70x90 cm	<i>Packing</i>	146x76x92 cm

Refrigerated counters
REFRIGERATED COUNTER -2°C ÷ +10°C DEPTH 70 CM WITH WORKTOP