

## REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT WORKTOP

Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Finned evaporator outside storage compartment, electric fan. Automatic defrosting by hot gas. Automatic condensation evaporation. Digital thermometer-thermostat with communication port, HACCP alarm signalling. Without top. 2 doors.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption E24, kW/h	6,772
Energy consumption/year, kW/h	2472	Energy Efficiency Class	D
Energy Efficiency Index	74,54	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	51	Net usable volume, lt	161
N° doors	2	N° drawers	0
Refrigerant charge, kg	0,06	Refrigerant/GWP	R290/3
Refrigeration power -23,3°C W	658	Temperature range	-12/-24°C
Volume, gross, lt	290		

### Functional features

- With digital thermometer-thermostat with communication port, HACCP alarm signalling: high and low temperature, black-out, probe failure. These alerts are provided via visual and acoustic alarms; if the probe inside the chamber fails, the appliance continues operating on the basis of the mean compressor operating times prior to the malfunction.
- Automatic defrosting by hot gas.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

### Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	97 kg
-----------------	-----------------	------------	-------

# 5EAB



Gross Weight	107 kg	Electric Power	0,7 kW
Dimensions	140x70x84 cm	Packing	146x76x92 cm

Refrigerated counters  
REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT WORKTOP