

REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT WORKTOP



Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Finned evaporator outside storage compartment, electric fan. Automatic defrosting by hot gas. Automatic condensation evaporation. Digital thermometer-thermostat with communication port, HACCP alarm signalling. Without top. 2 doors. It can be connected via Ethernet to the APO.LINK – Industry 4.0 – portal for real-time control of the appliances, and to export and view the data log and process parameters.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy consumption, kWh/24h</i>	6,772
<i>Energy consumption/year, kWh/a</i>	2472	<i>Energy Efficiency Class</i>	D
<i>Energy Efficiency Index</i>	74,54	<i>Heavy duty cabinets</i>	This appliance is intended for use in ambient temperatures up to 40 °C
<i>LWA dB(A)</i>	51	<i>Net usable volume, lt</i>	161
<i>N° doors</i>	2	<i>N° drawers</i>	0
<i>Refrigerant charge, kg</i>	0,06	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power -23,3°C W</i>	658	<i>Temperature range</i>	-12/-24°C
<i>Volume, gross, lt</i>	290		

Functional features

- With digital thermometer-thermostat with communication port, HACCP alarm signalling: high and low temperature, black-out, probe failure. These alerts are provided via visual and acoustic alarms; if the probe inside the chamber fails, the appliance continues operating on the basis of the mean compressor operating times prior to the malfunction.
- Automatic defrosting by hot gas.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance' s outstanding reliability is also assured by the IP24 protection of its functional elements.
- It can be connected via Ethernet to the APO.LINK – Industry 4.0 – portal for real-time control of the appliances, and to export and view the data log and process parameters.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.
- It can be connected via Ethernet to the APO.LINK – Industry 4.0 – portal for real-time control of the appliances, and to export and view the data log and process parameters.

REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT WORKTOP

Refrigerated counters

view the data log and process parameters.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	97 kg
<i>Gross Weight</i>	107 kg	<i>Electric Power</i>	0,7 kW
<i>Dimensions</i>	140x70x84 cm	<i>Packing</i>	146x76x92 cm

Refrigerated counters
REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT WORKTOP