

## REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITH WORKTOP

Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Finned evaporator outside storage compartment, electric fan. Automatic defrosting by hot gas. Automatic condensation evaporation. Digital thermometer-thermostat with communication port, HACCP alarm signalling. One-piece structure in AISI 304 stainless steel. 3 doors.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption E24, kW/h	9,236
Energy consumption/year, kW/h	3371	Energy Efficiency Class	F
Energy Efficiency Index	89,01	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	59	Net usable volume, lt	241
N° doors	3	N° drawers	0
Refrigerant charge, kg	0,08	Refrigerant/GWP	R290/3
Refrigeration power -23,3°C W	899	Temperature range	-12/-24°C
Volume, gross, lt	434		

### Functional features

- With digital thermometer-thermostat with communication port, HACCP alarm signalling: high and low temperature, black-out, probe failure. These alerts are provided via visual and acoustic alarms; if the probe inside the chamber fails, the appliance continues operating on the basis of the mean compressor operating times prior to the malfunction.
- Automatic defrosting by hot gas.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

### Technical Data

## 5EBBM



*Working voltage* 230V 1N~ / 50Hz

*Net Weight* 149 kg

*Gross Weight* 161 kg

*Electric Power* 1 kW

*Dimensions* 185x70x90 cm

*Packing* 192x76x92 cm

Refrigerated counters  
REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITH WORKTOP