

## REFRIGERATED COUNTER -2°C ÷ +8°C DEPTH 70 CM GN 1/1 WITHOUT MOTOR WITHOUT WORKTOP

Inside/outside in AISI 304 stainless steel. One-piece structure, preset for remote cooling. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by heating elements. Evacuation of condensate under the compartment. Digital thermometer-thermostat. Without top. 1 door, 2 drawers.



|                          |                     |                                       |   |
|--------------------------|---------------------|---------------------------------------|---|
| <i>Climate class</i>     | 5 (+40°C, 40% R.H.) | <i>Energy Efficiency Class</i>        | product are excluded from the European energy classification label according to EU Regulation 2015/1094 |
| <i>LWA dB(A)</i>         | 20                  | <i>Net usable volume, lt</i>          | 137   |
| <i>N° doors</i>          | 1                   | <i>N° drawers</i>                     | 2   |
| <i>Refrigerant/GWP</i>   | R134a/1430          | <i>Refrigeration power at -10°C W</i> | 304   |
| <i>Temperature range</i> | -2/+8°C             | <i>Volume, gross, lt</i>              | 288   |

### Functional features

- The appliance is set up for operation with a remote group running with R134a refrigerant fluid.
- This product is equipped with a thermostatic valve and solenoid valve; not supplied: copper pipes, electrical cables for connection to the motor unit.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Evacuation of condensate under the compartment.
- Noise level <70 dBA.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- To connect to the specific remote freezing group.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Drain outlet for easy cleaning.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

### Technical Data

|                        |                               |                       |              |
|------------------------|-------------------------------|-----------------------|--------------|
| <i>Working voltage</i> | 220V/230V/240V 1N~ / 50÷60 Hz | <i>Net Weight</i>     | 89 kg        |
| <i>Gross Weight</i>    | 99 kg                         | <i>Electric Power</i> | 0,3 kW       |
| <i>Dimensions</i>      | 115x70x84 cm                  | <i>Packing</i>        | 121x76x92 cm |