

REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT MOTOR WITHOUT WORKTOP

Inside/outside in AISI 304 stainless steel. One-piece structure, preset for remote cooling. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by heating elements. Evacuation of condensate under the compartment. Digital thermometer-thermostat. Without top. 2 doors.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy Efficiency Class</i>	product are excluded from the European energy classification label according to EU Regulation 2015/1094
<i>LWA dB(A)</i>	20	<i>Net usable volume, lt</i>	298
<i>N° doors</i>	2	<i>N° drawers</i>	0
<i>Refrigerant/GWP</i>	R452A/2141	<i>Refrigeration power -23,3°C W</i>	495
<i>Temperature range</i>	-12/-24°C	<i>Volume, gross, lt</i>	576

Functional features

- The appliance is set up for operation with a remote group running with R452a refrigerant fluid.
- This product is equipped with a thermostatic valve and solenoid valve; not supplied: copper pipes, electrical cables for connection to the motor unit.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Evacuation of condensate under the compartment.
- Noise level <70 dBA.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- To connect to the specific remote freezing group.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

Technical Data

<i>Working voltage</i>	220V/230V/240V 1N~ / 50÷60 Hz	<i>Net Weight</i>	77 kg
<i>Gross Weight</i>	87 kg	<i>Electric Power</i>	0,62 kW
<i>Dimensions</i>	115x70x84 cm	<i>Packing</i>	121x76x92 cm

REFRIGERATED COUNTER -24°C ÷ -12°C DEPTH 70 CM GN 1/1 WITHOUT MOTOR WITHOUT WORKTOP

Refrigerated counters