

REFRIGERATED COUNTER -2°C ÷ +8°C DEPTH 70 CM GN 1/1 WITHOUT MOTOR WITH WORKTOP

Inside/outside in AISI 304 stainless steel. One-piece structure, preset for remote cooling. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by heating elements. Evacuation of condensate under the compartment. Digital thermometerthermostat. One- piece structure in AISI 304 stainless steel. 3 doors, 2 drawers.



CE

Climate class	5 (+40°C, 40% R.H.)	Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1094
LWA dB(A)	20	Net usable volume, It	298
N° doors	3	N° drawers	2
Refrigerant/GWP	R134a/1430	Refrigeration power at -10°C W	486
Temperature range	-2/+8°C	Volume, gross, lt	576

Functional features

- · The appliance is set up for operation with a remote group running with R134a refrigerant fluid.
- This product is equipped with a thermostatic valve and solenoid valve; not supplied: copper pipes, electrical cables for connection to the motor unit.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- · Evacuation of condensate under the compartment.
- Noise level <70 dBA.

Constructional features

- · One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- · Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- · To connect to the specific remote freezing group.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- · Easily removable magnetic gasket.
- · Easy removable AISI 304 stainless steel racks to support grids/containers.
- Drain outlet for easy cleaning.
- · Stainless steel height-adjustable feet (140 mm 200 mm).
- · Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, waterproof and fire -proof assuring high shock resistance level.
- $\cdot\,$ Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

Technical Data Working voltage 220V/230V/240V 1N~ / 50÷60 Net Weight 152 kg Gross Weight 167 kg Electric Power 0,3 kW



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90 web: www.angelopo.com - email: angelopo@angelopo.it 27/02/2024



Dimensions

205x70x90 cm

Packing

211x76x92 cm

🕘 ANGELO PO

REFRIGERATED COUNTER -2°C ÷ +8°C DEPTH 70 CM GN 1/1 WITHOUT MOTOR WITH WORKTOP Refrigerated counters

