

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WORKTOP WITH REAR SPLASHBACK

Refrigerated counter with internal and external one-piece structure made of AISI 304 stainless steel. Outside finned evaporator and motor fan. Automatic defrosting system by air. Automatic condensation evaporation. Digital thermometer-thermostat. Radiused rear splashback. 1 door, 3 drawers.



| | | | |
|--------------------------------|---------------------|-----------------------------|--|
| Climate class | 5 (+40°C, 40% R.H.) | Energy consumption, kWh/24h | 2,268 |
| Energy consumption/year, kWh/a | 828 | Energy Efficiency Class | D |
| Energy Efficiency Index | 39,06 | Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| LWA dB(A) | 46 | Net usable volume, lt | 125 |
| N° doors | 1 | N° drawers | 3 |
| Refrigerant charge, kg | 0,07 | Refrigerant/GWP | R290/3 |
| Refrigeration power at -10°C W | 465 | Temperature range | 0/+10°C |
| Volume, gross, lt | 290 | | |

Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance' s outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Refrigerated compartment with AISI 304 stainless steel easy removable racks to support grids/containers.
- Enclosed drawers with three-stage telescopic runners allowing containers to be lifted out vertically.
- Drawers dimensions cm 30.5 x 54.8 x 90 h.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick, rounded on the front side with 8,5 cm high rearsplashback. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.

Standard equipment

- Each compartment with door is delivered as standard with n. 1 GN 1/1 grid and a pair of stainless steel guides.

5MA13A



Optional

- Blue-Tooth thermostat-thermometer, temperature recorder, print terminal, various containers and / or grids, wheels.

Technical Data

| | | | |
|------------------------|-----------------|-----------------------|---------------|
| <i>Working voltage</i> | 230V 1N~ / 50Hz | <i>Net Weight</i> | 125 kg |
| <i>Gross Weight</i> | 135 kg | <i>Electric Power</i> | 0,28 kW |
| <i>Dimensions</i> | 140x70x98,5 cm | <i>Packing</i> | 146x76x100 cm |

Refrigerated counters
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WORKTOP WITH REAR SPLASHBACK