

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP

Refrigerated counter with internal and external one-piece structure made of AISI 304 stainless steel. Outside finned evaporator and motor fan. Automatic defrosting system by air. Automatic condensation evaporation. Digital thermometer-thermostat. One-piece structure in AISI 304 stainless steel. 1 door, 3 drawers.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption, kWh/24h	2,268
Energy consumption/year, kWh/a	828	Energy Efficiency Class	D
Energy Efficiency Index	39,06	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	46	Net usable volume, lt	125
N° doors	1	N° drawers	3
Refrigerant charge, kg	0,07	Refrigerant/GWP	R290/3
Refrigeration power at -10°C W	465	Temperature range	0/+10°C
Volume, gross, lt	290		

Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Refrigerated compartment with AISI 304 stainless steel easy removable racks to support grids/containers.
- Enclosed drawers with three-stage telescopic runners allowing containers to be lifted out vertically.
- Drawers dimensions cm 30.5 x 54.8 x 90 h.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.

Standard equipment

- Each compartment with door is delivered as standard with n. 1 GN 1/1 grid and a pair of stainless steel guides.

5MA13M



Optional

- Blue-Tooth thermostat-thermometer, temperature recorder, print terminal, various containers and / or grids, wheels.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	124 kg
<i>Gross Weight</i>	134 kg	<i>Electric Power</i>	0,28 kW
<i>Dimensions</i>	140x70x90 cm	<i>Packing</i>	146x76x92 cm

Refrigerated counters
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP