

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP

Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by air. Automatic condensation evaporation. Digital thermometer-thermostat. Without top. 2 doors, 4 drawers.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption, kWh/24h	3,271
Energy consumption/year, kWh/a	1194	Energy Efficiency Class	D
Energy Efficiency Index	52,23	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	46	Net usable volume, lt	194
N° doors	2	N° drawers	4
Refrigerant charge, kg	0,07	Refrigerant/GWP	R290/3
Refrigeration power at -10°C W	465	Temperature range	0/+10°C
Volume, gross, lt	434		

Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance' s outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	131 kg
Gross Weight	143 kg	Electric Power	0,28 kW

5MB4



Dimensions

190x70x84 cm

Packing

192x76x92 cm

Refrigerated counters
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP