

**REFRIGERATED COUNTER 0 ÷ +10°C**  
**DEPTH 70 CM GN 1/1**

Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by air. Automatic condensation evaporation. Electronic thermometer/thermostat. Without top. 2 doors, 4 drawers.



|                                |                     |                              |  |
|--------------------------------|---------------------|------------------------------|--|
| Climate class                  | 5 (+40°C, 40% R.H.) | Energy consumption E24, kW/h | 4,65   |
| Energy consumption/year, kW/h  | 1697                | Energy Efficiency Class      | D  |
| Energy Efficiency Index        | 68,1                | Heavy duty cabinets          | This appliance is intended for use in ambient temperatures up to 40 °C |
| LWA dB(A)                      | 50                  | Net usable volume, lt        | 274  |
| N° doors                       | 2                   | N° drawers                   | 4  |
| Refrigerant charge, kg         | 0,28                | Refrigerant/GWP              | R134a/1430   |
| Refrigeration power at -10°C W | 632                 | Temperature range            | 0/+10°C  |
| Volume, gross, lt              | 574                 |                              |  |

**Functional features**

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

**Constructional features**

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.

**Technical Data**

|                 |                 |                |         |
|-----------------|-----------------|----------------|---------|
| Working voltage | 230V 1N~ / 50Hz | Net Weight     | 151 kg  |
| Gross Weight    | 166 kg          | Electric Power | 0,43 kW |

# 5MC4



*Dimensions*

230x70x84 cm

*Packing*

235,5x75,5x90 cm

Refrigerated counters  
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM GN 1/1