

## REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 60 CM WITH WORKTOP

Inside and outside in AISI 304 stainless steel. One-piece structure, insulated doors. Cooling system with exterior finned evaporator, electric fan. Automatic defrosting system by air. Automatic condensation evaporation. Digital thermometer-thermostat. One-piece structure in AISI 304 stainless steel. 2 doors.



Climate class	5 (+40°C, 40% R.H.)	Depth with door open (cm)	96
Energy consumption, kWh/24h	1,858	Energy consumption/year, kWh/a	678
Energy Efficiency Class	B	Energy Efficiency Index	31,61
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C	LWA dB(A)	46
Net usable volume, lt	139	N° doors	2
N° drawers	0	Refrigerant charge, kg	0,07
Refrigerant/GWP	R290/3	Refrigeration power at -10°C W	465
Temperature range	0/+10°C	Volume, gross, lt	237

### Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- Satin finished door, side panels and control panel. Scotchbrite finishing. Polished interior finishing.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid cm 32.5x46.

### Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	99 kg
Gross Weight	109 kg	Electric Power	0,28 kW

# 5MJAM



*Dimensions*

140x60x90 cm

*Packing*

144x64,5x100,5 cm

Refrigerated counters  
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 60 CM WITH WORKTOP