

# 5VA



## REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP

One-piece structure made in special anti-fingerprint steel. CFC-free polyurethane insulation, 60 mm thick. Easy removable AISI 304 stainless steel rack bars. Automatic defrosting system by air. Automatic condensation evaporation. Supplied as standard each compartment: 2 AISI 304 stainless steel runners + 1 shelf. Digital thermometer-thermostat. Without top. 2 doors.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption, kWh/24h	2,063
Energy consumption/year, kWh/a	753	Energy Efficiency Class	B
Energy Efficiency Index	34,21	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	46	Net usable volume, lt	161
N° doors	2	N° drawers	0
Refrigerant charge, kg	0,07	Refrigerant/GWP	R290/3
Refrigeration power at -10°C W	465	Temperature range	0/+10°C
Volume, gross, lt	290		

### Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.
- Key-lock: optional

### Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	86 kg
Gross Weight	96 kg	Electric Power	0,28 kW



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90  
web: [www.angelopo.com](http://www.angelopo.com) - email: [angelopo@angelopo.it](mailto:angelopo@angelopo.it)

29/04/2022

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP

Refrigerated counters

# 5VA



*Dimensions*

140x70x84 cm

*Packing*

146x76x92 cm

Refrigerated counters  
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITHOUT WORKTOP



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90  
web: [www.angelopo.com](http://www.angelopo.com) - email: [angelopo@angelopo.it](mailto:angelopo@angelopo.it)

29/04/2022