

## REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP

One-piece structure made in special anti-fingerprint steel. CFC-free polyurethane insulation, 60 mm thick. Easy removable AISI 304 stainless steel rack bars. Automatic defrosting system by air. Automatic condensation evaporation. Supplied as standard each compartment: 2 AISI 304 stainless steel runners + 1 shelf. Digital thermometer-thermostat. One-piece structure in AISI 304 stainless steel. 1 door, 2 drawers.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption, kWh/24h	2,268
Energy consumption/year, kWh/a	828	Energy Efficiency Class	C
Energy Efficiency Index	38,68	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	46	Net usable volume, lt	137
N° doors	1	N° drawers	2
Refrigerant charge, kg	0,07	Refrigerant/GWP	R290/3
Refrigeration power at -10°C W	465	Temperature range	0/+10°C
Volume, gross, lt	290		

### Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.

### Constructional features

- One-piece construction with round inner corners to ease cleaning operation. CFC-free expanded polyurethane insulation.
- Insulation thickness: 60 mm.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Insulated door equipped with removable magnetic gaskets that assure an optimum closing. Self-closing device for openings less than 90°. AISI 304 stainless steel handle.
- Easily removable magnetic gasket.
- Easy removable AISI 304 stainless steel racks to support grids/containers.
- Stainless steel height-adjustable feet (140 mm - 200 mm).
- Evaporator with an anti-corrosion treatment
- Worktop, 54 mm high, made in AISI 304 stainless steel, 12/10 thick. Worktop featuring inside a sound-absorbent panel, water-proof and fire -proof assuring high shock resistance level.
- Each compartment is equipped with 1 pair of stainless steel runners and 1 grid 1/1 GN.
- Key-lock: optional

### Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	119 kg
-----------------	-----------------	------------	--------

REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP

Refrigerated counters

## 5VA2M



Gross Weight	129 kg	Electric Power	0,28 kW
Dimensions	140x70x90 cm	Packing	146x76x92 cm

Refrigerated counters  
REFRIGERATED COUNTER 0 ÷ +10°C DEPTH 70 CM WITH WORKTOP