

ELECTRIC HOT CUPBOARD, WITH SLIDING DOORS

AISI 304 stainless steel top 54 mm h with satin finish 12/10 mm thickness. Sound deadening waterproof panel underneath. AISI 304 stainless steel free-standing structure with satin finish, with sliding doors with double walled sandwich panel structure, middle shelf reinforced by omega. Ventilated heating, thermostatic control. Height-adjustable stainless steel feet.



Heating	yes	Rear splashback	no
Working side	Two working sides		

Functional features

- Sturdiness of the worktop due to the particular construction and use of AISI 304 stainless steel sheet, thickness 12/10 mm.
- Hygiene ensured by the materials used and by the totally "closed" structure of the worktop.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Easy cleaning ensured by the construction of the rear splashback made in one piece with the top.
- Height-adjustable stainless steel feet for leveling on the floor, equipped with a thermosetting plastic sole.
- Capacity in Ø 23 cm plates on the intermediate shelf: 684.
- Maximum load per shelf with evenly distributed load: 230 kg.
- Doors opening on one side.

Constructional features

- Worktop height 54 mm made of 1.2 mm thick AISI 304 stainless steel with sounddeadening water-proof panel.
- Self-supporting cabinet made entirely on sides, back, bottom and door in satin-finished and cold-bent AISI 304 stainless steel.
- Sliding doors, sliding on upper guides, double-skinned. Handle obtained by folding in a single piece with the door.
- Middle shelf that can be positioned in different heights made of AISI 304 stainless steel, with omega reinforcement.
- Heating by electric element, with protected fans positioned inside the compartment. Temperature control ensured by mechanical thermostat adjustable from 30°C to 90°C. Indicator light when the set temperature has been reached.
- Hexagonal feet in stainless steel with plastic sole, adjustable for leveling on the floor h = 150 (max h = 180) mm.

Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- CE approvals in respect of all directives and regulations.
- IPX4 protection rating.

Optional

- Swivelling wheels with brake.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	120 kg
Gross Weight	130 kg	Electric Power	2 kW
Dimensions	200x70x90 cm	Packing	200x75x100 cm