## A20Z2E



# ELECTRIC HOT CUPBOARD, BOTH SIDE SLIDING DOORS

18-10 stainless steel free-standing structure cold pressed, with satin finish. Double walledsandwich panel hinged door. Height adjustable feet. Suitable to be fixed to continuous work surface. AISI 304 stainless steel freestanding structure with satin finish, with double walled sandwich panel hinged door. Complete with middle shelf. Ventilated heating, thermostatic control. Double side opening. Height-adjustable stainless steel feet.





Working side

Two working sides

### **Functional features**

- · Model designed to accommodate a worktop.
- · Height-adjustable stainless steel feet for leveling on the floor, equipped with a thermosetting plastic sole.
- · Capacity in Ø 23 cm plates on the intermediate shelf: 684.
- · Maximum load per shelf with evenly distributed load: 230 kg.
- · Doors opening on two sides.

### **Constructional features**

- · Model without worktop.
- · Self-supporting cabinet made entirely on sides, back, bottom and door in satin-finished and cold-bent AISI 304 stainless steel.
- · Sliding doors, sliding on upper guides, double-skinned. Handle obtained by folding in a single piece with the door.
- Middle shelf that can be positioned in different heights made of AISI 304 stainless steel, with omega reinforcement.
- Heating by electric element, with protected fans positioned inside the compartment. Temperature control ensured by mechanical thermostat adjustable from 30°C to 90°C. Indicator light when the set temperature has been reached.
- Hexagonal feet in stainless steel with plastic sole, adjustable for leveling on the floor h = 150 (max h = 180) mm.

#### Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- · CE approvals in respect of all directives and regulations.
- · IPX4 protection rating.

Technical Data			
Working voltage	230V 1N~ / 50Hz	Net Weight	110 kg
Gross Weight	120 kg	Electric Power	2 kW
Dimensions	200x70x66 cm	Packing	205x75x95 cm

