

UPPER REFRIGERATED TOP FOR PIZZA, 330 MM DEPTH

Refrigerated display made of AISI 304 stainless steel. Insulated structure, static refrigeration with injected evaporator. Control panel with digital thermometer-thermostat and on-off switch. Useful tank for G.N containers (1/2, 1/4, 1/6, 1/9) h 150 mm. Supplied with: 2 holdbars.



<i>LWA dB(A)</i>	46	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power at -20°C W</i>	290	<i>Temperature ranges, °C</i>	+2/+10

Functional features

- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.
- For upper display: static refrigeration, with evaporator injected on the bottom and on the walls, with air circulation in the engine compartment with front intake and rear and side exit.

Constructional features

- Refrigerated display made of AISI 304 stainless steel, insulated. Control panel with digital thermometer-thermostat and on-off switch. To be completed with containers.
- Depth of the refrigerated display: 330 mm. For G.N. ½, max height 150 mm and relative sub-multiples.
- Refrigerant fluid of the refrigerated display: R290.
- Evaporator with an anti-corrosion treatment.

Optional

- For refrigerated display: G.N. in various formats.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	70 kg
<i>Gross Weight</i>	75 kg	<i>Electric Power</i>	0,16 kW
<i>Dimensions</i>	259x33x26 cm	<i>Packing</i>	263,5x42,5x34 cm